



Cebo Holland

Product Data Sheet



Cebo F-SEAL Industrial Drilling

Description & Properties

Cebo F-SEAL is an acid soluble granulated **lost circulation material** of synthetic resin-bound **stone wool**. Cebo F-SEAL can be used as an additive for loss of circulation in concentrations of up to 20 kg/m³. Cebo F-SEAL is **inorganic and non-fermenting**. Cebo F-SEAL is **easily-wetted**.

Typical properties

<u>Parameter</u>	<u>Test method / In accordance with</u>	<u>Requirement</u>	<u>Typical property</u>
Composition			Synthetic resin-bound stone wool
Colour			Tan/brown
Form			Flocks
Smell			Odourless

Recommended treatment:

Cebo F-SEAL material can be added directly through the hopper. For **normal treatment** to the active system, add 3 - 10 kg/m³ drilling fluid.

As a **pill**, add 10 - 20 kg/m³ of drilling fluid.

Cebo F-SEAL is available in 20 kg bags.

In so far as we can ascertain the above-stated information is correct. However, we are unable to provide any guarantees with regard to the results that you will achieve with this. This specification is provided on the condition that you determine yourself to what degree it is suitable for your purposes.

Date : 16.04.2020
Document number : 502003GBR

Contact us for more information

Cebo Holland BV

Westerduinweg 1
NL-1976 BV IJmuiden
The Netherlands

info@cebo.com
www.cebo.com
Tel. +31(0)255-546262

